


**DECLARATION OF PERFORMANCE (DoP)**

1. Unique identification code of the product type : Q-CERAM tiles.  
See appendix 1.
2. Type, batch or serial number or any other element allowing identification of the product. Dry-pressed ceramic tiles with water absorption  $E_b \leq 0,5 \%$ .
3. Intended use(s) :  
For final finishing of internal and external walls and floorings. If necessary, pay attention to the information provided on the packaging and or catalogue before installation of the product.
4. Name of registered trade mark and contact address of the manufacturer.  
Company name : IMPEXBUILD EDS BVBA  
Address : Meengracht 9, B – 9620 Zottegem; Belgium  
Phone number : +32 9 367 95 31  
Fax number : +32 9 361 15 10  
E-mail : info@qceram.eu
5. Systems of assessment and verification of constancy of performance (AVCP). Systems 4, according European regulations EC.DIN-EN 14411-2012.
6. Name and identification number of notified laboratory.  
Not applicable. Tests done.
7. Declared performances

| Essential characteristics                                    | Performance  | Harmonized technical specifications |
|--|--|-------------------------------------|
| Reaction to fire   | A1 FL  | DIN-EN 14411-2012                   |
| Release of dangerous substances for :<br>• Cadmium<br>• Lead | Not intended use on worktops/wall surface where food preparation takes place |                                     |
| Breaking strength  | $\geq 2000$  |                                     |
| Slip resistance  | See appendix 1.  |                                     |
| Tactility  | NPD  |                                     |
| Thermal shock resistance                                     | No defect was found after test   |                                     |
| Durability for :<br>• internal use<br>• external use         | Pass   |                                     |
| Module of rupture  | $\geq 35$ MPa  |                                     |
| Resistance against sudden changes of temperature             | Required and resistant EN & ISO 10545/09                                     |                                     |

The performance of the product identified in point 1. is in conformity with the declared performances in point 7. This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by :

  
EDDY DE SMET, General Manager  
IMPEX BUILD EDS BVBA

**Impex Build EDS B.V.B.A.**  
Meengracht 9  
9620 Zottegem - Belgium  
Tel: +32 9 367 95 31  
Fax: +32 9 361 15 10  
E-mail: info@impexbuildeds.be  
BTW/TVA: BE 0479 742 204

Zottegem, July 1, 2013

Zottegem, March 1st, 2016

| Series  | Colour     | DIN 51130 |
|---------|------------|-----------|
| EMOTION | Black      | R9        |
|         | Dark grey  | R9        |
|         | Light grey | R9        |

|        |            |    |
|--------|------------|----|
| ENERGY | Dark grey  | R9 |
|        | Light grey | R9 |

|       |       |     |
|-------|-------|-----|
| BETON | light | R10 |
|       | mid   | R10 |
|       | dark  | R10 |

|       |            |    |
|-------|------------|----|
| METAL | Dark grey  | R9 |
|       | Light grey | R9 |

|          |       |     |
|----------|-------|-----|
| ETERNITY | black | R10 |
|          | grey  | R10 |
|          | ivory | R10 |

|       |            |    |
|-------|------------|----|
| INDEX | Light grey | R9 |
|       | Mid grey   | R9 |
|       | dark grey  | R9 |

|      |       |    |
|------|-------|----|
| BORA | Black | R9 |
|      | White | R9 |

**Impex Build EDS B.V.B.A.**  
 Meengracht 9  
 9620 Zottegem - Belgium  
 Tel: +32 9 367 05 31  
 Fax: +32 9 367 15 10  
 E-mail: info@impexbuildeds.be  
 BTW/TVA: BE 0479 742 204